





DESCRIPTION

A fully-assembled single-swing gate for the patented ecFence privacy fence system, built on a powder-coated galvanized steel frame and latched with a gravity latch or similar (no lockbox). ecStarter and ecPanel courses install into the frame with hidden fasteners to match the adjacent fence face. Available in standard ecFence finish colors, for residential and commercial perimeter applications.


DRAWINGS



ELEVATION — FRONT



ISOMETRIC — FRONT



ISOMETRIC — BACK

SPECIFICATIONS

Frame	2 × 1 in	Width (A)	35, 47, 59, 71, 83, 95 in
Panel infill	ecStarter + ecPanel (PPGL steel)	Height	70 in (5 ft 10 in)
Coating	Powder coat per AAMA 2603	Style	Single swing
Fasteners	3/4 in self-drilling screws	Wind rating	115 mph (Exp. C)
Hinges	ecGate Hinge (sold separately)	Engineering ref	ecFence S-1*



PATENTED



DURABLE



ROT-PROOF



TERMITE-PROOF



LOW
MAINTENANCE



PRIVACY



MODERN
LOOK



HIDDEN
FASTENERS



EASY TO
INSTALL



25 YEAR
WARRANTY**

FINISH COLORS

PRODUCTION

● Natural Bronze ○ Arctic White

COMING SOON

● Foggy Gray ● Midnight Black

INSTALLATION & FASTENING

MOUNTING

Hang on two ecGate Hinges (sold separately) to a 2.5 in HSS hinge post. Adjustable hinges set the gate-to-post gap; self-closing return is built in.

STANDARD SIZES

Nominal	Width (A)	Nominal	Width (A)
3 ft	35 in	6 ft	71 in
4 ft	47 in	7 ft	83 in
5 ft	59 in	8 ft	95 in

A = overall gate width. Single-swing standard sizes.

LATCHING

Latches with a gravity latch or similar latching mechanism — not included.

STORAGE & HANDLING

Store assembled gates upright on edge protectors or flat on a clean pallet, indoors or under fully waterproof cover. Combined sun and rain on packaging materials may stain the powder-coat finish.

Engineered to FBC 2023 HVHZ (ASCE 7-22), PE-sealed. Wind ratings are per fence height. Installations over 6 ft to 8 ft require a 3 in (76.2 mm) × 3 in (76.2 mm) post (specified; supplied by others) set per Drawing S-1 (8 ft). PE-sealed drawings for permitting available from ecFence.

*Standard sizes engineered to 8 ft maximum width; sealed engineering provided at permit submission.

**25-year warranty covers the ecPanel and ecStarter panels only; the powder-coated frame carries a 5-year coating warranty.